


Saturn 8000

4343V

View it now. You will know.


The most appropriate choice you can make.



High MTF & DQE
Pixel Pitch : 140 μm



Load Limit
of 400 KG



IP67

30 min in
1 m water depth

Saturn 8000 4343 V

Versatile Portable Flat Panel Detector for Digital Radiography



anytime™



Vieworks' proprietary AED
(Automatic Exposure Detection)

EASY

ISO 4090 :
same size as
a film/CR cassette



Temperature Stability



100 cm

100 cm Drop Test



fast wireless communication

inside AP™



Saturn 8000 4343V

Model Name	FXRD-4343VAW / FXRD-4343VAW PLUS
Technology	a-Si TFT
Scintillator	CsI
Pixel Pitch	140 μm
Spatial Resolution	3.5 lp/mm
Pixel Matrix	3072 x 3072 pixels
Image Size	43.0 cm x 43.0 cm
Grayscale	16 bits
Image Acquisition Time	3 s
Recommended Cycle Time	4 s
Data Interface	Gigabit Ethernet IEEE 802.11n / ac
X-ray Generator Interface	DR Trigger Mode / AED Mode
Dimensions	46.0 cm x 46.0 cm x 1.5 cm
Weight	3.5 kg (one battery) 3.7 kg (two batteries)
Battery	Lithium Ion 3400mAh x 2 14 h (standby) * 2,500 images at a 15-second cycle.
Dust and Water Resistant	IP67
X-ray Voltage Range	40 - 150 kVp
Operating Environment	0°C to 40°C 5 % to 90 % RH (non-condensing)
Power Consumption	Normal: Max. 24W, Charging: Max. 80W



Sales Office

3F., NO.32, Sec. 2, Zhongyang S. Rd., Beitou Dist., Taipei City 11270, Taiwan
Tel +886-2-2892-2275 Fax +886-2-2892-2172 E-mail Sales@newmedical.com.tw
www.nmi-dr.com



Factory

41-3, Burim-ro 170beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14055
Republic of KOREA

